



Nominal Flow : 150L	Internal Leakage A(B)→T : 5cm ³ / min.
Max. Flow : 170L	(T Δp100 bar - 1450psi with fluid and valve at 40°C, Oil viscosity 46cST)
Max. Operation Pressure : 350 bar	P-A-B-C Working Pressure : 320 bar
Max. Back Pressure (T) : 20 bar	Fluid Temperature : with NBR seals from - 20° to 80°C
Port Size : Inlet P G 3/4	with FPM seals from - 20° to 100°C
A and B ports G 3/4	Max. level of contamination : 19/16 - ISO 4406
Outlet T G 1	Weight : -

	NAME	DATE	MATERIAL	EN-GJL-250
DRAWER	FD	21.05.2018	G. TOLERANCE	--
CHECKING	ZT	21.05.2018	HARDNEES	--
SCALE	150L GS16/5/AC(X-200)/P5DY-5DY13NZL/ P5DY-5DY13NZL/P5DY-5DY13NZL/18L/18L/RC			
--				

	CODE	DRAWING NO
	15050021	2018.057

GÜRMAKSAN
 HYDRAULIC COMPONENTS LTD.CO.
 e-mail: info@gurmaksan.com.tr
 http://www.gurmaksan.com.tr

